

Liberator Surface Mount Phone

The Liberator phone meets all safety standards by providing the built-in features necessary to promptly connect, identify, and respond to calls for assistance.

The momentary press of the phone activating button puts it all into motion...

An automatic dialer is provided to dial out to an auxiliary location. In buildings that are not manned 24/7, multiple phone numbers can be programmed that will sequentially cycle through if there is no answer or a busy signal is detected. The recordable voice message is used to identify location and provide any dispatch and/or other information specific to the site. Automatic shut-off ensures units are always ready for the next call.



Just 1" deep!

Features

- Vandal Resistant
- Hands-free Speakerphone
- Five number automatic dialer
- Built-in keypad & remote programming
- Automatic & programmable shut-off
- Non-volatile memory
- Braille label & visual indicator
- Two voice announcement messages
- Voice prompted programming
- Automatic answer & shut-off
- Metal pushbutton
- Weather Protected Option

Applications

- Elevators
- Wheelchair Lifts
- Areas of Rescue
- Parking Garages
- Hallways
- Poolside
- Entry
- Security
- Campus
- Gated Areas
- Hospitals
- Safety Compliance
- Government Buildings
- Airports
- Malls

Liberator

Surface Mount Phone

Specifications	K-Phone ET401	SUREphone ET901
Analog Phone Line 24-51 VDC 30 mA	•	
24-51 VDC 20 mA		•
Power Requirements Phone line	•	
120 VAC 50 mA (includes battery backup)		•
Wiring 20 AWG shielded twisted pair	•	•
Approvals FCC (US), IC (Canada)	•	•
UL (US), CSA (Canada)	•	•
ADA (US)	•	•
ASME A17 (US), B44 (Canada)	•	•
Number of Phones per Phone Line One phone	•	
One to ten phones (independently addressed)		•
Intercom Option (SUREcom ET92)		•
Weather Protected Option	•	•

Dimensions		Weight
Standard Size:	6.75 H x 6.25 W x 1.0 D (In) 172 H x 159 W x 26 D (mm)	2 lbs 0.91 kg

Part Numbers	Options	Accessories
ET401A-LPSS-2	Add -WP Weather Protected *	ET-SP Surge Protector
ET901A-LPSS-2	-B Bronze/Muntz Faceplate	ET-92 SUREcom Intercom
*Weather protected option includes: Conformal coated circuit board, soldered connections and sealed contacts, water proof speaker and microphone		
Other styles available for Phone Box, Flush and OEM/Panel mounting.		

Specifications subject to change without prior notice.

K-Tech International, Inc.
56 Ella Grasso Ave.
Torrington, CT 06790

Phone: 800-993-9399 or 860-489-9399
FAX: 860-489-4399
www.KTechOnline.com