

**Low Cost Solution For Providing
Communications From
MACHINE ROOM and/or LOBBY
TO ELEVATORS**

[Ref: A17.1 2.26.1.5.10, 1996-2000]

and

**EMERGENCY PERSONEL—CALL IN-
PROGRESS OVERRIDE**

[Ref: A17.1 2.27.1.1.4, 2002-2007]



Features include ...

- Communications from Machine Room and/or Lobby to elevator (s) - up to 10
- Contact one or all elevators on system
- Use with new or existing K-Tech SUREphones
- Easy to install - modular RJ11 jacks and screw terminals for quick and easy wire connections.
- Easy to use - Pick-up Machine Room or Lobby intercom handset and automatically be connected to elevator SUREphone(s). Hang up to disconnect.
- Economical - Shares elevator emergency SUREphone(s) and wiring.

Specifications ET92 SUREcom

Wiring: 20 AWG shielded twisted pair
Power: 120 VAC Hz 16W Power Cube
 Output 18V DC 600mA
 (Battery backup included)

Specifications subject to change without prior notice.

Enclosure:
 Dimensions: 9" X 9" X 3" D
 Material: U.L. listed flame retardant thermoplastic alloy
Machine Room or Lobby: Surface Mount Handset model ET105 (1) included with ET92
Elevators: Use any K-Tech SUREphone ET901 Series II (purchased separately)